

Technical data Corode filter unit

CF07..S

6600l/h – Filter housing PP

Corode unit with seal pump **CPS-07**.

Q max :7m³/h

Q min :1.4m³/h

Q nominal :5.9m³/h

Pump head :PP

Motor : 0.55kW, 400V, 2.3/1.3Amp, 3Ph, 50Hz, IP55

Suitable for hot sealing processes.

Filter housing in PP maximum temp 80°C

Outside metal SS316

Height filter housing: 10",20"

Standard units include:

Terminal overload protection

Air release and drain valve

Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector

Hand priming pump

Transport wheels

Precoat tank PP 10"xØ225 (10 liter)

20"xØ225 (20 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
CF07CS PP	45	35	85	Ø32mm	Ø32mm	Cartridge 7x10"	2.31
CF07PS PP	45	35	85	Ø32mm	Ø32mm	Paper 41xØ215	1.25
CF07C20S PP	45	35	115	Ø32mm	Ø32mm	Cartridge 7x20"	4.62
CF07P20S PP	45	35	115	Ø32mm	Ø32mm	Paper 77xØ215	2.30

www.Corode.eu

tel: +31 (0)161-244250

corode@corode.nl