

## Technical data Corode filter unit

# CF20..S

### 21000l/h – Filter housing PP

Corode unit with with seal pump **CPS-20**.

Q max :20m<sup>3</sup>/h

Q min :4m<sup>3</sup>/h

Q nominal :14m<sup>3</sup>/h

Pump head :PP

Motor : 1.5kW, 400V, 5.4/3.2Amp, 3Ph, 50Hz, IP55

#### Suitable for hot sealing processes.

Filter housing in PP maximum temp 80°C

Outside metal SS316

Height filter housing: 20", 30"

#### Standard units include:

Terminal overload protection

Air release and drain valve

Pressure gauge

#### Filter media:

Cartridge, paper

#### Optional:

Dry run protector

Hand priming pump

Transport wheels

Precoat tank PP 20"xØ310 (36 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m <sup>2</sup>
<b>CF20CS PP</b>	60	50	120	Ø50mm	Ø50mm	Cartridge 15x20"	9.90
<b>CF20PS PP</b>	60	50	120	Ø50mm	Ø50mm	Paper 66xØ295	4.30
<b>CF20C30S PP</b>	60	50	145	Ø50mm	Ø50mm	Cartridge 15x30"	14.85
<b>CF20P30S PP</b>	60	50	145	Ø50mm	Ø50mm	Paper 95xØ295	6.45

[www.Corode.eu](http://www.Corode.eu)

tel: +31 (0)161-244250

corode@corode.nl