

Technical data Corode filter unit

CFJ30..M Jumbo

30000l/h – Filter housing PP

Corode unit with magnetic drive pump **MAG-30**.

Q max :30m³/h

Q min :6m³/h

Q nominal :18m³/h

Pump head :PP

Motor :2.2kW, 400V, 7.4/4.3Amp, 3Ph, 50Hz, IP55

Filter housing in PP maximum temp 80°C

Outside metal SS316

Height filter housing: 10", 20"

Standard units include:

Thermal overload switch

Air release/ drain valve

Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector

Hand priming pump

Transport wheels

Precoat tank PP 10"xØ500 (50 liter)

20"xØ500 (100 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
FILJ30CM PP	70	70	120	Ø50mm	Ø50mm	Cartridge 36x10"	11.88
FILJ30PM PP	70	70	120	Ø50mm	Ø50mm	Paper 35xØ456	6.00
FILJ30C20M PP	70	70	150	Ø50mm	Ø50mm	Cartridge 36x20"	23.76
FILJ30P20M PP	70	70	150	Ø50mm	Ø50mm	Paper 62xØ456	12.00

www.Corode.eu

tel: +31 (0)161-244250

corode@corode.nl