


Technical data Corode filter unit

CF04..M

3700l/h – Filter housing PP or PVDF

Corode unit with magnetic drive pump **CPMD-04**.

Q max :3.7m³h
 Q min :0.6m³h
 Pump head :PP or PVDF
 Motor :0.12kW, 400V, 0.76/0.44Amp, 3Ph, 50Hz, IP55
 :0.12kW, 230V, 1.1Amp, 1Ph, 50Hz, IP55
Other voltage options and 60Hz available on request.



Filter housing in PP maximum temp 80°C
 Filter housing in PP maximum temp 100°C
 Outside metal SS316
 Height filter housing: 10", 20"

Standard units include:

Thermal overload switch
 Air release/ drain valve
 Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector
 Hand priming pump
 Transport wheels
 Precoat tank PP 10"xØ225 (10 liter)
 20"xØ225 (20 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
CF04C3M PP	45	35	85	Ø25mm	Ø25mm	Cartridge 3x10"	0.99
CF04P3M PP	41	35	85	Ø25mm	Ø25mm	Paper 39xØ136	0.45
CF04C32M PP	45	35	110	Ø25mm	Ø25mm	Cartridge 3x20"	1.98
CF04P32M PP	45	35	110	Ø25mm	Ø25mm	Paper 75xØ136	0.90
CF04CM PP	45	35	85	Ø25mm	Ø25mm	Cartridge 7x10"	2.31
CF04PM PP	45	35	85	Ø25mm	Ø25mm	Paper 41xØ215	1.25
CF04C20M PP	45	35	110	Ø25mm	Ø25mm	Cartridge 7x20"	4.62
CF04P20M PP	45	35	110	Ø25mm	Ø25mm	Paper 77xØ215	2.30
CF04C3M PVDF	45	35	85	Ø25mm	Ø25mm	Cartridge 3x10"	0.99
CF04C32M PVDF	45	35	110	Ø25mm	Ø25mm	Cartridge 3x20"	1.98
CF04C5M PVDF	45	35	85	Ø25mm	Ø25mm	Cartridge 5x10"	1.65

www.corode.eu

tel: +31 (0)161-244250

corode@corode.nl