


Technical data Corode filter unit

CF11..M

11000l/h – Filter housing PP or PVDF material

Corode unit with magnetic drive pump **CPMD-11**.

Q max :11m³/h
 Q min :2 m³/h
 Pump head :PP or PVDF
 Motor :0.55kW, 400V, 2.3/1.3Amp, 3Ph, 50Hz, IP55
 :0.55kW, 230V, 5Amp, 1Ph, 50Hz, IP55
Other voltage options and 60Hz available on request.



Filter housing in PP maximum temp 80°C
 Filter housing in PVDF maximum temp 100°C
 Outside metal SS316
 Height filter housing: 10", 20"

Standard units include:

Thermal overload switch
 Air release/ drain valve
 Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector
 Hand priming pump
 Transport wheels
 Precoat tank PP 10"xØ310 (18 liter)
 20"xØ310 (36 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
CF11CM PP	55	45	90	Ø38mm	Ø38mm	Cartridge 15x10"	4.95
CF11PM PP	55	45	90	Ø38mm	Ø38mm	Paper 37xØ295	2.20
CF11C20M PP	55	45	115	Ø38mm	Ø38mm	Cartridge 15x20"	9.90
CF11P20M PP	55	45	115	Ø38mm	Ø38mm	Paper 66xØ295	4.30
CF11C7M PP	55	45	115	Ø38mm	Ø38mm	Cartridge 7x20"	4.62
CF11P7M PP	55	45	115	Ø38mm	Ø38mm	Paper 77xØ215	2.30
CF11C52M PVDF	55	45	115	Ø38mm	Ø38mm	Cartridge 5x20"	1.65

www.corode.eu

tel: +31 (0)161-244250

corode@corode.nl