

Technical data Corode filter unit

CF15..M

20400l/h – Filter housing PP

Corode unit with magnetic drive pump **CPMD-15**.

Q max :20.4m³/h
 Q min :4m³/h
 Q nominal :12m³/h
 Pump head :PP
 Motor :1.1kW, 400V, 3.82/2.22Amp, 3Ph, 50Hz, IP55
Other voltage options and 60Hz available on request.

Filter housing in PP maximum temp 80°C

Outside metal SS316

Height filter housing: 10", 20"

Standard units include:


Thermal overload switch
 Air release/ drain valve
 Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector
 Hand priming pump
 Transport wheels
 Precoat tank PP 10"xØ310 (18 liter)
 20"xØ310 (36 liter)



	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
CF15CM PP	60	50	95	Ø38mm	Ø38mm	Cartridge 15x10"	4.95
CF15PM PP	60	50	95	Ø38mm	Ø38mm	Paper 37xØ295	2.20
CF15C20M PP	60	50	120	Ø38mm	Ø38mm	Cartridge 15x20"	9.90
CF15P20M PP	60	50	120	Ø38mm	Ø38mm	Paper 66xØ295	4.30

www.corode.eu

tel: +31 (0)161-244250

corode@corode.nl