

Technical data Corode filter unit

FIL04..M

3500l/h – Filter housing PP

Corode unit with magnetic drive pump **MAG-04**.

Q max :3.5m³/h
 Q min :0.6m³/h
 Pump head :PP or PVDF
 Motor :0.12kW, 400V, 0.66/0.38Amp, 3Ph, 50Hz, IP55
 :0.12kW, 230V, 1.1Amp, 1Ph, 50Hz, IP55

Filter housing in PP maximum temp 80°C
 Filter housing in PP maximum temp 100°C
 Outside metal SS316
 Height filter housing: 10", 20"

Standard units include:

Thermal overload switch
 Air release/ drain valve
 Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector
 Hand priming pump
 Transport wheels
 Precoat tank PP 10"xØ225 (10 liter)
 20"xØ225 (20 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
FIL04C3M PP	45	35	85	Ø25mm	Ø25mm	Cartridge 3x10"	0.99
FIL04P3M PP	41	35	85	Ø25mm	Ø25mm	Paper 36xØ136	0.45
FIL04C32M PP	45	35	110	Ø25mm	Ø25mm	Cartridge 3x20"	1.98
FIL04P32M PP	45	35	110	Ø25mm	Ø25mm	Paper 75xØ136	0.90
FIL04CM PP	45	35	85	Ø25mm	Ø25mm	Cartridge 7x10"	2.31
FIL04PM PP	45	35	85	Ø25mm	Ø25mm	Paper 41xØ215	1.25
FIL04C20M PP	45	35	110	Ø25mm	Ø25mm	Cartridge 7x20"	4.62
FIL04P20M PP	45	35	110	Ø25mm	Ø25mm	Paper 77xØ215	2.30
FIL04C3M PVDF	45	35	85	Ø25mm	Ø25mm	Cartridge 3x10"	0.99
FIL04C32M PVDF	45	35	110	Ø25mm	Ø25mm	Cartridge 3x20"	1.98
FIL04C5M PVDF	45	35	85	Ø25mm	Ø25mm	Cartridge 5x10"	1.65

www.corode.eu

tel: +31 (0)161-244250

corode@corode.nl