

## Technical data Corode filter unit

# FIL04B.M Bag filter

### 3500l/h – Filter housing PP

Corode unit with magnetic drive pump **MAG-04**.

Q max :3.5m<sup>3</sup>/h  
 Q min :0.6m<sup>3</sup>/h  
 Pump head :PP or PVDF  
 Motor :0.12kW, 400V, 0.66/0.38Amp, 3Ph, 50Hz, IP55  
 :0.12kW, 230V, 1.1Amp, 1Ph, 50Hz, IP55

Filter housing in PP maximum temp 80°C

Outside metal SS316

Height filter housing: 20", 30"

#### Standard units include:

Thermal overload switch

Air release/ drain valve

Pressure gauge

#### Filter media:

Bag filter 400xØ180 or 800xØ180

#### Optional:

Dry run protector

Hand priming pump

Transport wheels



	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m <sup>2</sup>
<b>FIL04B20M PP</b>	45	35	110	Ø25mm	Ø25mm	Bag 400xØ180	-
<b>FIL04B30M PP</b>	45	35	135	Ø25mm	Ø25mm	Bag 800xØ180	-

[www.corode.eu](http://www.corode.eu)

tel: +31 (0)161-244250

corode@corode.nl